

Specification

Dimensions (L × W × H)

Total Weight

Mounting / Orientation

Casing Design & Material

Cooling Method

Battery Voltage, nominal

Battery Capacity (Ah)

Battery Capacity Usable (Ah)

Battery Energy (Wh)

Battery Chemistry

Cycle Life

Depth of Discharge (%)

Continious Discharge

Continious Charge

Operating Charge Temperature Range

Operating Discharge Temperature Range

optimal operating and storage temperature

Front Panel Display

Built in features

Connections

Output Voltage(s)

Max Continuous Output

Peak / Surge Output

Topo Plug & Play accessories

Plug & Play Expandability

Warranty

T-CF72AH

301 x 142 x 215

10.33Kg

Space saving flush mount connector design

Tough Steel Casing
collapsible ergonomic carry handle
No exposed terminals

Fan cooled

12.8V
72AH
65AH
832Wh
LiFePO4
>2000
Recommened 80%
50A
70A
0 to 50 degree celcious
0 to 50 degree celcious
25degree c

LED SOC 5 Bar
LED Status Indicators
SOC Resolution (20%)
Built-in Net Positive/Negative Amp Meter

Built in Topo 40A DC-DC Vehicle Input (Blue)
Topo Voltage Sense- Topo Dual battery voltage controller

Topo Solar controller (Red) – Max 25A
Topo Mains Charger Input (Yellow)

Inputs- Clearly labeled, individually colour coded and keyed
1x Heavy Duty 50A Blue Anderson Connector – Input Only
1x Heavy Duty Mini 35A Red Connector – Input Only
1x Heavy duty mini 35A Yellow Connector – Input Only

Outputs- Clearly labeled, individually colour coded and keyed
1x Heavy Duty 50A Grey Anderson Connector (Rated 50A)
2x Heavy Duty Mini 35A Grey Connector (Rated 40A combined)

12v - 14.2v
50a
65a

Topo Magnetic Distribution boards
Topo Wireless Monitor
Topo 10A Mains Charger
Topo USB adaptor

12V / Pure Sine Wave Inverter (recommended 500W-1000W max)
Max 600W continuous discharge from 50A Grey Anderson output

Topo Tinny Mate 12V/100AH

24 months workshop warranty on all electronics
5 years on battery cells

T-CF100AH

288 x 138 x 245

11.15Kg

Space saving flush mount design

Tough Steel Casing
collapsible ergonomic carry handle
No exposed terminals

Fan cooled

12.8V
100AH
100AH
1280Wh
LiFePO4
>3000
Recommened 80%
100Amps
50Amps
0 to 55 degree celcious
0 to 55 degree celcious
25degree c

LED SOC 10 Bar
LED Status Indicators
SOC Resolution (10%)
Built-in Amp Meter

Topo 40A DC-DC Vehicle Input (Blue)
Topo Voltage Sense - Dual battery voltage controller

Topo Solar controller (Red) – Max 25A
Topo Mains Input (Yellow)

Inputs- Clearly labeled, individually colour coded and keyed
1x Heavy Duty 50A Blue Anderson Connector – Input Only
1x Heavy Duty 50A Red Anderson Connector – Input Only
1x Heavy duty mini 35A Yellow Connector – Input Only

Outputs- Clearly labeled, individually colour coded and keyed
2x Heavy Duty 50A Grey Anderson Connector (Rated 100A Combined)
1x Heavy Duty Mini 35A Grey Connector (Rated 20A)

12v- 14.2v
100A
100A

Topo Magnetic Distribution boards
Topo Wireless Monitor
Topo 10A Mains Charger
Topo USB adaptor

12V / Pure Sine Wave Inverter (recommended 1000W max)
Max 1200W continuous discharge from 2x 50A Grey Anderson outputs
Topo InstantHeat PortaStove

Topo Tinny Mate 12V/100AH

24 months workshop warranty on all electronics
5 years on battery cells

T-CF100AH-DD

288 x 138 x 245

11.86kg

Space saving flush mount design

Tough Steel Casing
collapsible ergonomic carry handle
No exposed terminals

Fan cooled

12.8V	
100AH	
100AH	
1280Wh	
LiFePO4	35% More power
>3000	
Recommended 80%	
100Amps	
50Amps	
0 to 55 degree celcius	
0 to 55 degree celcius	
25degree c	

LED SOC 10 Bar
LED Status Indicators
SOC Resolution (10%)
Built-in Amp Meter

Topo 40A DC-DC Vehicle Input (Blue)
Topo Voltage Sense - Dual battery voltage controller

Topo Solar controller (Red) – Max 25A
Topo Mains Input (Yellow)

Inputs- Clearly labeled, individually colour coded and keyed
1x Heavy Duty 50A Blue Anderson Connector – Input Only
1x Heavy Duty 50A Red Anderson Connector – Input Only
1x Heavy duty mini 35A Yellow Connector – Input Only

Outputs- Clearly labeled, individually colour coded and keyed
2x Heavy Duty 50A Grey Anderson Connector (Rated 100A Combined)
1x Heavy Duty Mini 35A Grey Connector (Rated 20A)
1x Heavy Duty DIRECT DRIVE mini Connector to Suit Topo InstantHeat PortaStove

12v - 14.2v
100A
100A

Topo Magnetic Distribution boards

Topo Wireless Monitor

Topo 10A Mains Charger

Topo USB adaptor

12V / Pure Sine Wave Inverter (recommended 1000W max)
Max 1200W continuous discharge from 2x 50A Grey Anderson outputs
Topo InstantHeat PortaStove-Direct Drive

Topo Tinny Mate 12V/100AH

24 months workshop warranty on all electronics
5 years on battery cells